### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.

# W. F. Taylor Co., Inc.

11545 Pacific Avenue Fontana, CA 92337-8228 951/360-6677 CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: MSPlus Advance Wood Flooring Adhesive

ITEM NUMBER: MSPLUS-4

ITEM DESCRIPTION: MSPlus Advance Wood Flooring Adhesive 4-gal.

PRODUCT DESCRIPTION: Low Viscosity Wood Adhesive CHEMICAL FAMILY: MS Polymer- Resin Blend

REVISION DATE: 01/07/10

HMIS HAZARD RATING

LEAST: 0 HEALTH: 1 SLIGHT: 1 FLAMMABLE: 0 MODERATE: 2 REACTIVITY: 0

HIGH: 3 EXTREME: 4

PREPARED BY: DARWIN C. REGIS
PREEMPTS PREVIOUS MSDS SHEETS

### SECTION II HAZARDOUS INGREDIENTS

COMPONENT/CAS # ACGIH TLV OSHA PEL % WT NOTES

NO HAZARDOUS INGREDIENTS PER CURRENT OSHA REGULATIONS NON HAZARDOUS PER DIRECTIVE 67/548/EEC AND 1999/45/EC

### SECTION III PHYSICAL DATA

BOILING POINT: NO DATA

LBS / GAL: 10.75 - 11.05

EVAPORATION RATE: LOW VAPOR DENSITY: LOW VAPOR PRESSURE: LOW

PERCENT VOLATILE: 0( BY WEIGHT), 100% SOLIDS

COLOR: OFF WHITE

ODOR: MILD

GRAMS V.O.C. PER LITER OF MATERIAL: 0.5

### SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT, PENSKY-MARTIN C.C.: NA

AUTO IGNITION TEMPERATURE, DEGREES F: NA

FLAMMABLE LIMITS IN AIR (% BY VOLUME): LEL: NA UEL: NA

EXTINGUISHING MEDIA:

(X) WATER SPRAY (X) CARBON DIOXIDE ( ) OTHER

(X) FOAM (X) DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: USE SELF CONTAINED BREATHING APPARATUS AND TURN OUT GEAR. WATER MAY BE INEFFECTIVE BUT SHOULD BE USED TO KEEP THE EXPOSED CONTAINERS COOL. UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN

(Continued) Page 2

PRODUCT NAME: MSPlus Advance Wood Flooring Adhesive

ITEM NUMBER: MSPLUS-4

ITEM DESCRIPTION: MSPlus Advance Wood Flooring Adhesive 4-gal.

REVISION DATE: 01/07/10

### SECTION V HEALTH HAZARD IDENTIFICATION

SYMPTOMS OF OVER EXPOSURE:

INHALATION: MAY CAUSE SLIGHT IRRITATION TO THE UPPER RESPIRATORY TRACT.

EYES: VAPOR MAY CAUSE IRRITATION.

SKIN: MAY CAUSE SLIGHT SKIN IRRITATION.

INGESTION: NOT A LIKELY ROUTE OF ENTRY UNDER PROPER HANDLING CONDITIONS. MAY CAUSE

VOMITING. SYMPTOMS MAY BE SAME AS INHALATION.

HEALTH EFFECTS OR RISK FROM EXPOSURE:

ACUTE: INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTACT WITH EYES AND SKIN MAY

RESULT TO IRRITATION. INGESTION MAY RESULT TO GASTRIC DISTURBANCES.

CHRONIC: NOT KNOWN

#### FIRST AID PROCEDURES:

EYES CONTACT: WASH WITH WATER AT LEAST 15 MINUTES. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.

SKIN CONTACT: REMOVE FROM SKIN AND WASH WITH SOAP AND WATER. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. ADMINISTER OXYGEN, IF NECESSARY. SEEK MEDICAL ATTENTION.

INGESTION: IF SWALLOWED, CALL PHYSICIAN.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE KNOWN

# SECTION VI REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: PROTECT FROM FREEZING, EXCESSIVE HEAT.

INCOMPATIBILITY (MATERIALS TO AVOID): METAL SALTS MAY COAGULATE THE PRODUCT.

HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): OXIDES OF CARBON, WATER,

AND ORGANIC COMPOUNDS OF UNKNOWN STRUCTURE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

#### SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED

KEEP OUT OF SEWER SYSTEMS TO PREVENT BLOCKAGE DUE TO POLYMER DEPOSITS. SCRAPE UP TO COLLECT AND PLACE INTO CLOSED CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL: ABIDE BY ALL STATE, FEDERAL AND LOCAL REGULATIONS.

### SECTION VIII SPECIAL PROTECTION INFORMATION

VENTILATION AND ENGINEERING CONTROLS: USE LOCAL EXHAUST. DO NOT USE CLOSED

AIR-CIRCULATING SYSTEM. OPEN WINDOWS AND DOORS IF NECESSARY.

RESPIRATORY PROTECTION: NIOSH RESPIRATOR IF NEEDED.

CLOTHING: CHEMICAL RESISTANT GLOVES, APRON, COVERALLS, AND BOOTS AS NECESSARY TO PREVENT CONTACT.

EYE PROTECTION: CHEMICAL GOGGLES OR FACE SHIELD

OTHER CLOTHING AND EQUIPMENT: IF CLOTHING BECOMES CONTAMINATED, REMOVE AND CLEAN BEFORE REWEARING.

WORK PRACTICES, HYGIENIC PRACTICES: FOLLOW LABEL INSTRUCTIONS.

PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: USE GOGGLES AND GLOVES WHEN CLEANING ADHESIVE FROM EQUIPMENT. MAINTAIN PROPER VENTILATION.

(Continued) Page 3

PRODUCT NAME: MSPlus Advance Wood Flooring Adhesive

ITEM NUMBER: MSPLUS-4

ITEM DESCRIPTION: MSPlus Advance Wood Flooring Adhesive 4-gal.

REVISION DATE: 01/07/10

### SECTION IX SPECIAL PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN. DO NOT INDUCE VOMITING IF INGESTED. AVOID BREATHING BUILDUP OF VAPORS. USE WITH ADEQUATE VENTILATION.

PROTECT AGAINST PHYSICAL DAMAGE. STORE IN A COOL DRY PLACE (50 - 90 DEGREES F). KEEP AWAY FROM HEAT AND SPARKS. KEEP FROM FREEZING.

## SECTION X TOXICOLOGICAL PROPERTIES

NOT KNOWN

# SECTION XI REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD(29CFR 1910.1200)HAZARD CLASS(ES): NONE SARA TITLE III SECTION 312 HAZARD CLASS: NONE EPA SARA TITLE III SECTION 313: NONE

#### NOTICE

W.F. TAYLOR BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS OF THE DATE HEREOF. TAYLOR MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION.